

CHARGING SYSTEMS AND CAR ACCESSORIES 2023/2024



THE EINHELL GUARANTEE PROMISE.

We develop our products so that you can make everything possible. Our priority here is functionality, safety and quality. That is our promise and this is backed up by our guarantees too.

- **Einhell Product Warranty**
Warranty extension for all Einhell products to 3 years.
- **PurePOWER Brushless Warranty**
Warranty extension for all PurePOWER Brushless products to 10 years.*
- **30 Day Money-Back Guarantee**
For 100% satisfaction with your Power X-Change device.
- **Power X-Change Battery Warranty**
Warranty extension for Power X-Change batteries to 3 years.



* This warranty covers only defects in the engine that are due to a material or manufacturing defect!

THIS IS HOW:

Find out more at einhell.de, register in your customer account and apply for the warranty.

Further information is available at www.einhell.de/en/services/warranties/

einhell.de
>>>





POWER X-CHANGE

Power X-Change | Cordless Excellence that convinces. 4



STARTING / CHARGING SYSTEMS

| | | | |
|--|----|-------------------------|----|
| Jump-Start - Power Banks | 8 | Analog Battery Chargers | 13 |
| Microprocessor-Controlled Battery Chargers | 10 | Booster Cables | 14 |



CAR ACCESSORIES


| | | | |
|------------------------------------|----|--------------------------------------|----|
| Cordless Impact Wrenches | 15 | Car Air Compressors | 20 |
| Impact Wrenches | 15 | Cordless Car Air Compressor | 21 |
| Car Hammer Screwdriver | 16 | Cordless Compressors | 22 |
| Trolley Jack | 16 | 6-in-1 Cordless Hybrid Compressors | 23 |
| Cordless Car Polishing Machine | 17 | 3-in-1 Cordless Compressors | 23 |
| Car Polishing Machine | 17 | Cordless Wet and Dry Vacuum Cleaners | 24 |
| Cordless Polishing/Sanding Machine | 18 | Cordless Stick Vac Cleaner | 26 |
| Polishing and Sanding Machines | 19 | Cordless Handheld Vacuum Cleaners | 26 |
| Cordless Air Pump | 20 | Power X-Change Accessories | 28 |



**CORDLESS FREEDOM.
FOR WORKSHOP, GARDEN AND
YOUR ENTIRE HOME.**

At last – no more too short or severed cables.

When you no longer have to worry about extension cables that are too short or sufficient sockets. When the device comes to the project instead of the other way round. When you simply insert the battery and are ready to go, whether it is a lawn mower, garden pump, rotary hammer or wet and dry vacuum cleaner. That is the feeling of cordless freedom.



**LATEST TECHNOLOGY.
PROVEN QUALITY.**

For the highest level of safety and performance.

Power X-Change batteries are the core component of our platform. That's why we use only the best components such as high-performance new-generation cells and our intelligent processor-controlled battery electronics. This makes our PXC battery one of the safest in the industry and ensures efficiency, reliability and durability.



**POWERFUL MACHINES.
LONG-LASTING BATTERIES.**

No matter how large your project – Power X-Change won't let you down.

Less power? No way! As a battery system for real enablers, our cordless machines offer up to 2700 Watt of battery power and 8 Ah of capacity, making them easily a match for corded machines! Whether you just want to hang a shelf or drill through a solid concrete wall, with Power X-Change you are equipped to meet any challenge with power and endurance.



**1 BATTERY. 1000 POSSIBILITIES.
FOR DIY ENTHUSIASTS AND HOBBY
GARDENERS.**

Just as versatile as you: Battery power for every situation.

Power X-Change is the first rechargeable battery system that provides hobby gardeners and DIY enthusiasts alike with an unrivaled selection of cordless tools. The PXC family already contains over 300 devices. To enable us to offer you cordless freedom in even more areas of life, we have opened our platform to strong partners. Thanks to the versatile Power X-Change system diverse items from partner companies are "Powered by Power X-Change".



ACTIVE BATTERY MANAGEMENT SYSTEM. INTELLIGENT ELECTRONIC CONTROL SYSTEM.

The computer-assisted Active Battery Management System permanently monitors and controls all the safety-related processes of the electrical components and associated hardware. This results in a whole range of advantages:

- MAXIMISED RUNNING TIMES
- OPTIMISED TOOL POWER
- LONGER BATTERY SERVICE LIFE
- INCREASED SAFETY



TWIN-PACK TECHNOLOGY. 18 V + 18 V = 36 V.

If a device needs more power than provided by a single 18 V rechargeable battery, we simply add a second battery so we generate 18 V + 18 V = 36 V. We call that Twin-Pack Technology.


If the voltage (V) gets doubled, the power (W) gets doubled, too. Double Twin-Pack Technology in turn makes it possible to work for even longer still without the nuisance of recharging. In this case, four rechargeable batteries are used. When the power of the first two batteries finally runs out, the system automatically switches over to the two additional batteries.



POWER X-CHANGE PLUS. THE PLUS IN POWER

Rechargeable batteries vary not just in terms of running time and weight. What is also critically important is the power that they provide. With Power X-Change PLUS Technology you get more power per cell, so that you can work with plenty of power even on challenging applications as well.

If, for example, you want to use your angle grinder for cutting work, the running time (see Ah rating) is generally not critical. Sufficient power, on the other hand, is. A car is a useful comparison. Uphill or when overtaking, more power, in other words more hp respectively kW, is needed.



PUREPOWER – BRUSHLESS DRIVE TECHNOLOGY FOR THE HIGHEST DEMANDS.

Various Power X-Change devices are equipped with brushless motors. They offer significant advantages compared to carbon brush motor:

- MORE POWER
- LONGER RUNNING TIMES
- LONGER SERVICE LIFE
- MORE COMPACT DESIGN
- MAINTENANCE-FREE



PUREPOWER
BRUSHLESS

- + 25% power*
- + 50% endurance*
- + 100% lifetime*
- + 10 years warranty**

*Approximate values in comparison to conventional carbon brush motors. **On brushless motors, upon online registration.

CORDLESS EXCELLENCE.

CONVINCING. AGAIN AND AGAIN.



"We are incredibly proud to regularly get the best marks in competition with our strongest rivals, underlining our cordless expertise with rechargeable batteries."

Andreas Kroiss, CEO of Einhell Germany AG



CORDLESS EXCELLENCE THAT CONVINCES. ONLY BY EINHELL.

It became clear to us early on that our customers wanted the freedom of cordless operation. We decided accordingly to concentrate fully on the sector of cordless technology and on the expansion of our Power X-Change system of rechargeable batteries. In numerous product tests carried out by prestigious trade journals and independent experts we have been rewarded with "top marks" and the position of "best in the

test", confirming the outstanding quality of our products and underlining Einhell's bundled competence. It is our aim to inspire our customers with Einhell cordless power and to provide them with freedom, fun and enjoyment on all their jobs around the house and garden. This will make Power X-Change a synonym for cordless freedom.



JUMP-START – POWER BANKS


12 V / 300 A JUMP START
For dead/flat car batteries

Jump-Start – Power Bank
CE-JS 18/1

USB OUTLETS
Charge mobile phones, smart phones, tablet PCs, cameras, MP3 players, etc.

LED WORK LIGHT
Continuous illumination, strobe light and SOS emergency signal

JUMP START CABLES
With fully insulated terminal clamps and overload protection



CHARGING CONNECTION
for 230 V charging adapter

12 V AND 19 V OUTPUT
For laptops, car compressors, ...

LED CHARGE STATUS INDICATOR

ON SWITCH



WHAT IS A JUMP START – POWERBANK?

High-performance power reserves.
2-in-1 handy helper in your vehicle: handy jump start and power bank in one.



WHICH JUMP-START – POWERBANK FOR WHICH VEHICLE?

| | |  |  |  |
|--|---|---|---|---|
| | | CE-JS 18/1 | CE-JS 12/1 | CE-JS 8/1 |
|  ≤ 3000 cm ³ |  Petrol | ● | ● | ● |
|  ≤ 4000 cm ³ |  Petrol | ● | ● | ● |
|  ≤ 8000 cm ³ |  Petrol | ● | ● | ● |
|  ≤ 2000 cm ³ |  Diesel | ● | ● | ● |
|  ≤ 5000 cm ³ |  Diesel | ● | ● | ● |

● Suitable ● Not suitable

JUMP-START – POWER BANKS



| | CE-JS 18/1 CAR EXPERT | CE-JS 12/1 CAR EXPERT | CE-JS 8/1 CAR EXPERT |
|---|--|--|---------------------------------------|
| Capacity | 3 x 6000 mAh (66.6 Wh) | 3 x 3700 mAh (41.1 Wh) | 3 x 2500 mAh (27.75 Wh) |
| Start voltage | 12 V | 12 V | 12 V |
| Start current / peak current | 300 A / 600 A | 200 A / 400 A | 200 A / 400 A |
| USB outlet | 5 V / 2 A und 3 A | 5 V / 2 A und 3 A | 5 V / 2 A und 3 A |
| Consumption outlet | 12 V 10 A / 19 V 3.5 A | 12 V 10 A / 19 V 3.5 A | - |
| For petrol engines up to | 8000 cm ³ | 4000 cm ³ | 3000 cm ³ |
| For diesel engines up to | 5000 cm ³ | 2000 cm ³ | - |
| Charging time | 6 h | 5 h | - |
| Product weight | 0.7 kg | 0.5 kg | 0.4 kg |
| Jump start function and power bank | • | • | • |
| Booster cable | • | • | • |
| LED charge status indicator | • | • | • |
| LED work light | • | • | • |
| Charging function for cell phone / tablet PC / camera | • | • | • |
| Charging function for notebook / laptop | • | • | - |
| USB adapter cable (Micro/Mini USB) | • | • | • |
| Adapter cable with 9 notebook adapters | • | • | - |
| 230 V charging adapter | • | • | - |
| USB charging cable | - | - | • |
| Storage case | • | • | • |
| Article number | 10.915.31 | 10.915.21 | 10.915.11 |



4 006825 626353



4 006825 626346



4 006825 626339



IMPRESSIVE FEATURES.

Virtually indispensable in the car: the power bank is a handy jump starter in case of battery breakdown, and you can also use it to charge your mobile phone, tablet PC and other devices.



SMART CELL CONTROL

- Maximum performance thanks to lithium polymer rechargeable batteries
- Optimum output at all times
- Maximum battery life



JUMP START

- For dead car batteries
- Jump starting without external h
- Practically always ready for action thanks to minimal self-discharge



DOUBLE TEMPERATURE MONITORING

- Maximum user safety
- Perfect protection against damage



LED WORK LIGHT

Highly useful in emergencies:

- Steady-on to provide illumination
- Strobe light or SOS emergency signal light in case of accident/breakdown



POWER BANK

Power bank / mobile power supply for mobile phones, tablets, laptops, cameras, etc.



NO RISK OF APPLICATION ERRORS

thanks to the reverse polarity protection

INTELLIGENT CHARGERS.

FULLY AUTOMATIC, USER-FRIENDLY AND GENTLE ON THE BATTERY.



ALL-PURPOSE CHARGERS



EASY TO USE



EXTENDED BATTERY LIFE



WINTER CHARGING MODE



SAFE TO USE



INCREASE AND MAINTAIN BATTERY CAPACITY



OPTIMAL STATE OF CHARGE AT ALL TIMES



RECONDITION MODE FOR CHARGING DEEPLY DISCHARGED BATTERIES



MULTI-STAGE CHARGING CYCLE FOR LOW-STRESS CHARGING OF THE BATTERIES



POWER SUPPLY MODE FOR A POWER SUPPLY WHILE CHANGING THE BATTERY

THE RIGHT CHARGER FOR EVERY USE.

| Charging time (hours)** | CE-BC 1 M | CE-BC 2 M | CE-BC 4 M | CE-BC 5 M LiFePO4 | CE-BC 6 M | CE-BC 10 M | CE-BC 15 M | CE-BC 30 M | * |
|-------------------------|------------|-----------|-----------|-------------------|-----------|------------|------------|-------------|--------|
| Charging voltage | 6 V / 12 V | 12 V | 12 V | 12 V | 12 V | 12 V | 12 V | 12 V / 24 V | |
| | ● 4 h | ● 2 h | ● | ● | ● | ● | ● | ● | 4 Ah |
| | ● 12 h | ● 6 h | ● 3 h | ● | ● | ● | ● | ● | 12 Ah |
| | ● 18 h | ● 9 h | ● 5 h | ● 4 h | ● 3 h | ● | ● | ● | 18 Ah |
| | ● | ● | ● 11 h | ● 9 h | ● 8 h | ● | ● | ● | 45 Ah |
| | ● | ● | ● 18 h | ● 14 h | ● 12 h | ● 7 h | ● | ● | 70 Ah |
| | ● | ● | ● | ● | ● 17 h | ● 10 h | ● 7 h | ● | 100 Ah |
| | ● | ● | ● | ● | ● | ● 12 h | ● 8 h | ● | 120 Ah |
| | ● | ● | ● | ● | ● | ● 15 h | ● 10 h | ● | 145 Ah |
| | ● | ● | ● | ● | ● | ● 18 h | ● 12 h | ● | 180 Ah |
| | ● | ● | ● | ● | ● | ● | ● | ● 13 h | 200 Ah |

● Very suitable ● Suitable ● Less suitable ● Not suitable

Info

Chargers with microprocessor control are suitable for gel, AGM, low-maintenance and maintenance-free leadacid batteries.

Select the charger that matches the size of your battery. The higher the charge current (A) provided by the charger, the faster the battery gets charged. A charger which provides a charging current equal to 1/10 of the battery capacity is ideal. 60 Ah → 6 A.

* Frequently installed battery sizes

** Charging times are subject to variation. The times given assume that battery charging takes place at the maximum current output of the charger. The charging time also depends on the battery charge state. Chargers with a lower amperage can certainly also be used for pure trickle charging.

MICROPROCESSOR-CONTROLLED BATTERY CHARGERS



| | CE-BC 30 M CAR EXPERT | CE-BC 15 M CAR EXPERT |
|---|--|--|
| Mains connection | 230 V ~ 50 Hz | 230 V ~ 50 Hz |
| Charging voltage | 12 V / 24 V | 12 V |
| Suitable for batteries (min. / max. Ah) | 3 - 600 Ah | 3 - 300 Ah |
| Charging current max. | 15 A (on 24 V) / 30 A (on 12 V) | 15 A |
| Product weight | 11.0 kg | 7.0 kg |
| Multi-step charging cycle, microprocessor-controlled | • | • |
| Suitable for gel batteries / AGM batteries / lead-acid batteries | • | • |
| Suitable for Lithium Iron Phosphate Batteries | - | - |
| Boost engine output (rms) | 100 A - 5 sek | 100 A - 5 sek |
| Winter charging mode | • | • |
| Totally insulated battery terminals | • | • |
| Electronic overcharging, short-circuit & swapped poles protection | • | • |
| Trickle charge function | • | • |
| Recondition + power supply mode | - | - |
| Force Function | - | - |
| Dustproof / splashproof | IP 20 | IP 20 |
| Integrated wall bracket / handle | • | • |
| Article number | 10.022.75 | 10.022.65 |



MICROPROCESSOR-CONTROLLED BATTERY CHARGERS



| | CE-BC 10 M CAR EXPERT | CE-BC 6 M CAR EXPERT | CE-BC 5 M LiFePO4 CAR EXPERT |
|---|--|---------------------------------------|---|
| Mains connection | 220 - 240 V ~ 50 Hz | 220 - 240 V ~ 50 Hz | 220 - 240 V ~ 50 Hz |
| Charging voltage | 12 V | 12 V | 12 V |
| Suitable for batteries (min. / max. Ah) | 3 - 200 Ah | 3 - 150 Ah | 5 - 120 Ah |
| Charging current max. | 10 A | 6 A | 5 A |
| Product weight | 0.7 kg | 0.6 kg | 0.6 kg |
| Multi-step charging cycle, microprocessor-controlled | • | • | • |
| Suitable for gel batteries / AGM batteries / lead-acid batteries | • | • | • |
| Suitable for Lithium Iron Phosphate Batteries | - | - | • |
| Boost engine output (rms) | - | - | - |
| Winter charging mode | • | • | • |
| Totally insulated battery terminals | • | • | • |
| Electronic overcharging, short-circuit & swapped poles protection | • | • | • |
| Trickle charge function | • | • | • |
| Recondition + power supply mode | • | • | • |
| Force Function | - | - | • |
| Dustproof / splashproof | IP 65 | IP 65 | IP 65 |
| Integrated wall bracket / handle | • | • | • |
| Article number | 10.022.45 | 10.022.35 | 10.022.51 |



MICROPROCESSOR-CONTROLLED BATTERY CHARGERS



| | CE-BC 4 M CAR EXPERT | CE-BC 2 M CAR EXPERT | CE-BC 1 M CAR EXPERT |
|---|--------------------------------|--------------------------------|--------------------------------|
| Mains connection | 220 - 240 V ~ 50 Hz | 220 - 240 V ~ 50 Hz | 220 - 240 V ~ 50 Hz |
| Charging voltage | 12 V | 12 V | 6 V / 12 V |
| Suitable for batteries (min. / max. Ah) | 3 - 120 Ah | 3 - 60 Ah | 3 - 32 Ah |
| Charging current max. | 4 A | 2 A | 1 A |
| Product weight | 0.4 kg | 0.3 kg | 0.2 kg |
| Multi-step charging cycle, microprocessor-controlled | • | • | • |
| Suitable for gel batteries / AGM batteries / lead-acid batteries | • | • | • |
| Suitable for Lithium Iron Phosphate Batteries | - | - | - |
| Boost engine output (rms) | - | - | - |
| Winter charging mode | • | • | - |
| Totally insulated battery terminals | • | • | • |
| Electronic overcharging, short-circuit & swapped poles protection | • | • | • |
| Trickle charge function | • | • | • |
| Recondition + power supply mode | • | - | - |
| Force Function | - | - | - |
| Dustproof / splashproof | IP 65 | IP 65 | IP 65 |
| Integrated wall bracket / handle | • | • | • |
| Article number | 10.022.25 | 10.022.15 | 10.022.05 |



ANALOG BATTERY CHARGERS



| | CC-BC 15 CAR CLASSIC | CC-BC 12 CAR CLASSIC |
|--|---------------------------------------|---------------------------------------|
| Mains connection | 230 V ~ 50 Hz | 230 V ~ 50 Hz |
| Charging voltage | 6 V / 12 V / 24 V | 12 V |
| Suitable for batteries (min. / max. Ah) | 10 - 300 Ah | 26 - 200 Ah |
| Charging current (eff.) on 6 V | min. 6.5 A / max. 15 A | - |
| Charging current (eff.) on 12 V | min. 8 A / max. 15 A | 12 A |
| Charging current (eff.) on 24 V | min. 7 A / max. 10 A | - |
| Product weight | 5.3 kg | 3.2 kg |
| Overload / false poling / short-circuit protection | • | • |
| Suitable for lead-acid batteries | • | • |
| Built-in ammeter | • | • |
| All-insulated construction | • | • |
| Totally insulated battery terminals | • | • |
| Boost engine output (rms) | - | - |
| Electronics with charging voltage limitation | - | - |
| Carry handle | • | • |
| Article number | 10.750.31 | 10.567.21 |



4 006825 613209



4 006825 613193

ANALOG BATTERY CHARGERS



| | CC-BC 10 E CAR CLASSIC | CC-BC 5 CAR CLASSIC |
|--|---|--------------------------------------|
| Mains connection | 230 V ~ 50 Hz | 230 V ~ 50 Hz |
| Charging voltage | 12 V | 12 V |
| Suitable for batteries (min. / max. Ah) | 5 - 200 Ah | 16 - 80 Ah |
| Charging current (eff.) on 6 V | - | - |
| Charging current (eff.) on 12 V | 10 A | 5 A |
| Charging current (eff.) on 24 V | - | - |
| Product weight | 2.8 kg | 2.0 kg |
| Overload / false poling / short-circuit protection | • | • |
| Suitable for lead-acid batteries | • | • |
| Built-in ammeter | • | • |
| All-insulated construction | • | • |
| Totally insulated battery terminals | • | • |
| Boost engine output (rms) | - | - |
| Electronics with charging voltage limitation | • | - |
| Carry handle | • | • |
| Article number | 10.508.21 | 10.561.21 |



4 006825 613186



4 006825 612660

BOOSTER CABLES



| | BT-BO 25/1 A LED SP CAR CLASSIC | BT-BO 25/1 A CAR CLASSIC |
|---------------------------|--|--|
| For petrol engines up to | 5500 cm ³ | 5500 cm ³ |
| For diesel engines up to | 3000 cm ³ | 3000 cm ³ |
| Battery voltage | 12 / 24 V | 12 / 24 V |
| Cable length | 3.5 m | 3.5 m |
| Cable cross section | 31.4 mm ² alu (= 25 mm ² copper) | 31.4 mm ² alu (= 25 mm ² copper) |
| Testing current | 350 A | 350 A |
| Product weight | 1.7 kg | 1.7 kg |
| All-insulated pole-pliers | • | • |
| Surge protection | • | - |
| Carrying bag | • | • |
| LED light | • | - |
| Article number | 20.303.65 | 20.303.45 |



BOOSTER CABLES



| | BT-BO 16/1 A LED SP CAR CLASSIC | BT-BO 16/1 A CAR CLASSIC |
|---------------------------|--|--|
| For petrol engines up to | 2500 cm ³ | 2500 cm ³ |
| For diesel engines up to | - | - |
| Battery voltage | 12 / 24 V | 12 / 24 V |
| Cable length | 3 m | 3 m |
| Cable cross section | 19.4 mm ² alu (= 16 mm ² copper) | 19.4 mm ² alu (= 16 mm ² copper) |
| Testing current | 220 A | 220 A |
| Product weight | 1.2 kg | 1.2 kg |
| All-insulated pole-pliers | • | • |
| Surge protection | • | - |
| Carrying bag | • | • |
| LED light | • | - |
| Article number | 20.303.60 | 20.303.35 |



POWER X-CHANGE
**CORDLESS
IMPACT WRENCHES**
PURE POWER
BRUSHLESS

PURE POWER
BRUSHLESS


| | IMPAXXO 18/400 PROFESSIONAL | IMPAXXO 18/230 PROFESSIONAL |
|--|--|--|
| PXC battery voltage / capacity | 18 V / - | 18 V / - |
| Charging time | - | - |
| Idle speed | 0 - 1000 / 0 - 1500 / 0 - 2000 min ⁻¹ | 0 - 2900 min ⁻¹ |
| Torque (hard) | 400 Nm | 230 Nm |
| Bit mount | 12.5 mm (1/2") external square drive mount | 12.5 mm (1/2") external square drive mount |
| Product weight | 2.0 kg (excl. battery) | 1.1 kg (excl. battery) |
| Brushless motor | • | • |
| LED | • | • |
| Metal gear box | • | • |
| Electronic speed control | • | • |
| Belt clip | • | • |
| Number of batteries / number of chargers | 0 / 0 | 0 / 0 |
| Bit adapter | • | • |
| Drive socket inserts (incl.) | 3 | - |
| Packaging | Colour box | Colour box |
| Article number | 45.100.70 | 45.100.80 |



4 006825 657456



4 006825 664317

IMPACT WRENCHES


| | CC-IW 950/1 CAR CLASSIC | CC-IW 450 CAR CLASSIC |
|--|--|--|
| Mains connection | 230 - 240 V ~ 50 Hz | 230 V ~ 50 Hz |
| Power rating | 950 W | 450 W |
| Idle speed | 2300 min ⁻¹ | 2600 min ⁻¹ |
| Max. torque | 450 Nm | 300 Nm |
| Tool mounting | 12.7 mm (1/2") external square drive mount | 12.7 mm (1/2") external square drive mount |
| Cable length | 2 m | 2 m |
| Product weight | 3.4 kg | 2.0 kg |
| Clockwise / Counterclockwise operation | • | • |
| Soft grip | • | • |
| Drive socket inserts (incl.) | 17, 19, 21, 22 mm (1 of each) | 17, 19, 21, 22 mm (1 of each) |
| Packaging | Colour box | Colour box |
| Article number | 42.599.51 | 20.483.04 |



4 006825 635829



4 006825 626186

CAR HAMMER SCREWDRIVER



| | CC-HS 12/2 CAR CLASSIC |
|--|--|
| Rated voltage | 12 V |
| Max. torque | 350 Nm (loosening torque) |
| Tool mounting | 12.7 mm (½") external square drive mount |
| Cable length | 3.5 m |
| Product weight | 1.5 kg |
| Clockwise / Counterclockwise operation | • |
| LED light | • |
| Drive socket inserts (incl.) | 17/19 mm, 21/23 mm |
| Packaging | Colour box |
| Article number | 20.483.13 |



TROLLEY JACK



| | CC-TJ 2000 CAR CLASSIC |
|---|----------------------------------|
| Load capacity | 2 t |
| Lifting height min. | 135 mm |
| Lifting height max. | 330 mm |
| Product weight | 8.7 kg |
| 2 ball bearing castors | • |
| Integrated carry handle | • |
| Support plate | • |
| Removable lift rod | • |
| Integrated safety valve against overloading | • |
| Article number | 20.117.79 |



POWER XCHANGE

CORDLESS CAR POLISHING MACHINE



| | CE-CB 18/254 Li - Solo CAR EXPERT |
|--------------------------------|--|
| PXC battery voltage / capacity | 18 V / - |
| Rotation speed | 2500 min ⁻¹ |
| Diameter | 254 mm |
| Product weight | 1.9 kg (excl. battery) |
| Member of the PXC family | • |
| ON/OFF switch | • |
| Ergonomic soft grip | • |
| Textile bonnet | 1 pc |
| Synthetic bonnet | 1 pc |
| Packaging | Colour box |
| Article number | 20.933.01 |



4 006825 626599

CAR POLISHING MACHINE



| | CC-PO 90 CAR CLASSIC |
|------------------|---------------------------------------|
| Mains connection | 230 V ~ 50 Hz |
| Power rating | 90 W |
| Rotation speed | 3700 min ⁻¹ |
| Diameter | 240 mm |
| Product weight | 1.9 kg |
| ON/OFF switch | • |
| Textile bonnet | 1 pc |
| Synthetic bonnet | 1 pc |
| Packaging | Colour box |
| Article number | 20.931.73 |



4 006825 614145

CORDLESS POLISHING/SANDING MACHINE

ELECTRONIC SPEED CONTROL
5 settings

ERGONOMIC HANDLE
for an optimum hold and controlled operation

SPINDLE LOCK
for easy attachment of the polishing disc

SLIMLINE DESIGN
with ergonomic softgrip surfaces

BRUSHLESS MOTOR
More power and prolonged operation

POLISHING DISC WITH HOOK-AND-LOOP FASTENER
for changing the attachments quickly

Cordless Polishing/Sanding Machine
CE-CP 18/180 Li E

PUREPOWER BRUSHLESS

EFFICIENT TECHNOLOGY
Eco POWER

POWER X-CHANGE

CORDLESS POLISHING/SANDING MACHINE



| | CE-CP 18/180 Li E - Solo EXPERT |
|--|--|
| PXC battery voltage / capacity | 18 V / - |
| Rotation speed | 500 - 3000 min ⁻¹ |
| Diameter | 180 mm |
| Product weight | 1.3 kg (excl. battery) |
| Member of the PXC family | • |
| Brushless motor | • |
| ON/OFF switch | • |
| Ergonomic soft grip | • |
| Speed electronics | • |
| Spindle lock | • |
| Hook and loop fastener for polishing/grinding acc. | • |
| Synthetic bonnet | 1 pc |
| Foam pad | 1 pc |
| Abrasive paper (grit size 60, 80, 120) | 1 of each |
| Packaging | Colour box |
| Article number | 20.933.20 |



POLISHING AND SANDING MACHINES



| | CC-PO 1100/1 E CAR CLASSIC | CC-PO 1100/150 E CAR CLASSIC | CC-PO 1100/2 E CAR CLASSIC |
|--|---|---|---|
| Mains connection | 230 V ~ 50 Hz | 230 V ~ 50 Hz | 230 V ~ 50 Hz |
| Power rating | 1100 W | 1100 W | 1100 W |
| Rotation speed | 1000 - 3500 min ⁻¹ | 1000 - 3500 min ⁻¹ | 1000 - 3500 min ⁻¹ |
| Diameter | 180 mm | 150 mm | 180 mm |
| Product weight | 2.5 kg | 2.5 kg | 2.3 kg |
| ON/OFF switch | • | • | • |
| Ergonomic soft grip | • | • | • |
| Speed electronics | • | • | • |
| Spindle lock | • | • | • |
| Hook and loop fastener for polishing/grinding acc. | • | • | • |
| Synthetic bonnet | 2 pcs | 2 pcs | 1 pc |
| Foam pad | 1 pc | 1 pc | 1 pc |
| Abrasive paper (grit size 60, 80, 120) | 2 of each | 2 of each | 1 of each |
| Packaging | Case | Case | Colour box |
| Article number | 20.932.64 | 20.932.75 | 20.932.65 |



4 006825 614169



4 006825 653618



4 006825 614176

ACCESSORIES – POLISHING MACHINES



| | Polishing Bonnets Set ACCESSORY | Polishing/Grinding Set 180 mm ACCESSORY | Polishing/Grinding Set 150 mm (incl. plate) ACCESSORY | Polishing/Grinding Set 150 mm (excl. plate) ACCESSORY |
|------------------|--|--|--|--|
| Can be used for | CE-CB 18/254 Li / CC-PO 90 | CC-PO 1100/1 E / CC-PO 1100/2 E / CE-CP 18/180 Li E | CC-PO 1100/1 E / CC-PO 1100/2 E / CE-CP 18/180 Li E | CC-PO 1100/150 E |
| Textile bonnet | 1 pc | - | - | - |
| Synthetic bonnet | 1 pc | 2 pcs | 2 pcs | 2 pcs |
| Foam pad | - | 1 pc | 1 pc | 1 pc |
| Abrasive paper | - | 6 pcs (grit size 60, 80, 120 – 2 of each) | 6 pcs (grit size 60, 80, 120 – 2 of each) | 6 pcs (grit size 60, 80, 120 – 2 of each) |
| Plate | - | - | 1 pc | - |
| Article number | 20.930.95 | 20.932.33 | 20.932.45 | 20.932.46 |



4 006825 631517



4 006825 551846



4 006825 653977



4 006825 655490

POWER X-CHANGE

CORDLESS AIR PUMP



| | CE-AP 18 Li - Solo CAR EXPERT |
|--------------------------------|---|
| PXC battery voltage / capacity | 18 V / - |
| Air rate | 670 l/min |
| Max. pressure | 0.05 bar |
| Product weight | 0.4 kg (excl. battery) |
| Member of the PXC family | • |
| Locking switch | • |
| Suitable for deflation | • |
| Valve adapter | 2x |
| LED | • |
| Suitable for | Rubber dinghies, air mattresses, leisure articles |
| Article number | 20.701.10 |



4 006825 658996

CAR AIR COMPRESSORS



| | CC-AC 35/10 12 V CAR CLASSIC |
|--------------------------------------|---|
| Mains voltage | 12 V |
| Max. operating pressure | 10 bar |
| Pressure hose length | 1500 mm |
| Product weight | 2.0 kg |
| Pressure gauge | 0 - 10 bar |
| Extra long connection cable | 2.8 m |
| Valve connection for car tyre valves | Schrader valve |
| Spare adapters (incl.) | 4 pcs (bike, water ball, air bed, ball adapter) |
| Article number | 20.721.21 |



4 006825 618327

| | CC-AC 12 V CAR CLASSIC |
|--------------------------------------|---|
| Mains voltage | 12 V |
| Max. operating pressure | 18 bar |
| Pressure hose length | 450 mm |
| Product weight | 0.6 kg |
| Pressure gauge | 0 - 18 bar |
| Extra long connection cable | 2.9 m |
| Valve connection for car tyre valves | Schrader valve |
| Spare adapters (incl.) | 3 pcs (water ball, air bed, ball adapter) |
| Article number | 20.721.12 |



4 006825 614114

CORDLESS CAR AIR COMPRESSOR



MANUAL INFLATION
without pressure preselect if the required pressure is unknown

INTEGRATED TYRE VALVE
with pressure hose 60 cm long

3-PIECE INFLATION ADAPTER SET
with integrated storage on the device

DIGITAL PRESSURE INDICATOR
for fast and easy reading of both the current and the previous pressure

PRESSURE PRESELECTION
A required pressure of up to max. 11 bar can be preselected

SHUT-OFF FUNCTION
Automatic shut-off function upon reaching the set pressure

ERGONOMIC HANDLE
for greater comfort during use

Cordless Car Air Compressor
CE-CC 18 Li



CORDLESS CAR AIR COMPRESSOR



| CE-CC 18 Li - Solo | |
|-----------------------------------|----------------------------------|
| CAR EXPERT | |
| PXC battery voltage / capacity | 18 V / - |
| Max. operating pressure | 11 bar |
| Pressure hose length | 600 mm |
| Product weight | 0.8 kg (excl. battery) |
| Member of the PXC family | • |
| Digital pressure indicator | • |
| Setting of the required pressure | • |
| Automatic switch-off | • |
| Manual pumping | • |
| 3-piece set of inflation adapters | • |
| Integrated accessory storage | • |
| Suitable for | Car tyres, cycle tyres and balls |
| Article number | 20.710.10 |



POWER X-CHANGE

CORDLESS COMPRESSORS



| | TE-AC 36/150 Li OF - Solo EXPERT NEW | TE-AC 36/8 Li OF Set - Solo EXPERT NEW |
|-----------------------------------|---|---|
| PXC battery voltage / capacity | 2x 18 V / - | 2x 18 V / - |
| Suction power | 150 l/min | 130 l/min |
| Output rate 0 bar 4 bar 7 bar | 95 l/min 70 l/min 50 l/min | 90 l/min 55 l/min 38 l/min |
| Tank capacity | 6 l | without pressure chamber |
| Max. operating pressure | 8 bar | 8 bar |
| Product weight | 9.7 kg (excl. batteries) | 5.4 kg (excl. batteries) |
| Member of the PXC family | • | • |
| Pressure reducer | • | - |
| Accessory storage | • | • |
| Compressed air hose | - | • |
| Blow-out adapter | - | • |
| Tyre Pressure Gauge | - | • |
| Adapter set | - | • |
| Article number | 40.204.15 | 40.204.40 |





6-IN-1 CORDLESS HYBRID COMPRESSORS



| | PRESSITO 18/25 Hybrid EXPERT | NEW | PRESSITO EXPERT |
|------------------------------------|--|------------|---|
| PXC battery voltage / capacity | 18 V / - | | 18 V / - |
| Mains connection | 220 - 240 V ~ 50/60 Hz | | 220 - 240 V ~ 50 Hz |
| Suction power | 25 l/min | | 21 l/min |
| Output rate 0 bar 4 bar 7 bar | 19 l/min 12 l/min 10 l/min | | 16 l/min 10 l/min 8 l/min |
| Max. operating pressure | 11 bar | | 11 bar |
| Product weight | 2.5 kg (excl. battery) | | 2.1 kg (excl. battery) |
| Member of the PXC family | • | | • |
| Hybrid function | • | | • |
| Digital pressure indicator | • | | • |
| Light | • | | - |
| Push button for high-pressure pump | • | | - |
| Cable storage | • | | • |
| Accessory storage | • | | • |
| Hoses incl. | High-pressure hose (71 cm), low-pressure hose (160 cm) | | High-pressure hose (71 cm), low-pressure hose (31 cm) |
| Adapter set | • | | • |
| Article number | 40.204.30 | | 40.204.60 |



3-IN-1 CORDLESS COMPRESSORS



| | PRESSITO 18/25 EXPERT | NEW | PRESSITO 18/21 EXPERT |
|------------------------------------|--|------------|---|
| PXC battery voltage / capacity | 18 V / - | | 18 V / - |
| Suction power | 25 l/min | | 21 l/min |
| Output rate 0 bar 4 bar 7 bar | 17 l/min 11 l/min 9 l/min | | 14 l/min 9 l/min 6 l/min |
| Max. operating pressure | 11 bar | | 10.5 bar |
| Product weight | 2.3 kg (excl. battery) | | 2.1 kg (excl. battery) |
| Member of the PXC family | • | | • |
| Push button for high-pressure pump | • | | • |
| Digital pressure indicator | • | | • |
| Accessory storage | • | | • |
| Hoses incl. | High-pressure hose (71 cm), low-pressure hose (160 cm) | | High-pressure hose (71 cm), low-pressure hose (31 cm) |
| Adapter set | • | | • |
| Article number | 40.204.20 | | 40.204.67 |



CORDLESS WET AND DRY VACUUM CLEANERS



Cordless Wet and Dry Vacuum Cleaner
TP-VC 36/30 S Auto

POWER X-CHANGE LITHIUM-ION BATTERY
Cordless operation means that corners and hard-to-reach areas are easy to sweep as well. The rechargeable battery can be used in all the devices from the Power X-Change family

ECO-/BOOST MODE
2 speeds (ECO + BOOST) for optimum battery use

ACCESSORY HOLDER
The TP-VC 36/30 S Auto is always ready for action thanks to the accessory holder directly on the equipment

TWIN-PACK
18V + 18V 36V
TECHNOLOGY

TWIN-PACK TECHNOLOGY
Using 2x 18 V Power X-Change rechargeable batteries delivers even more power

HEAVY-DUTY SUCTION HOSE
The 2.50 m hose is flexible and resistant to foot traffic at the same time

CONNECTIVITY FUNCTION
The connectivity function means that no cables are required to connect the vac. It starts up automatically when the cordless power tool is started

STAINLESS STEEL TANK
The 30 l stainless steel tank provides sufficient capacity for dirt and liquids

LARGE WHEELS AND CASTORS
Thanks to the 2 wheels and the 2 castors the wet and dry vacuum cleaner is easy to move about in the workshop, garage or living area

POWER X-CHANGE

CORDLESS WET AND DRY VACUUM CLEANERS



| | TP-VC 36/30 S Auto - Solo | NEW |
|---------------------------------|--|-----|
| | PROFESSIONAL | |
| PXC battery voltage / capacity | 2x 18 V / - | |
| Suction power | 150 mbar / 100 mbar (BOOST / ECO) | |
| Tank | Stainless steel, 30 l | |
| Product weight | 8.2 kg (excl. batteries) | |
| Member of the PXC family | • | |
| Automatic starting system | • | |
| Speed settings | 2 | |
| Also suitable for wet vacuuming | • | |
| Suction hose | Plastic 250 cm, heavy-duty material | |
| Suction tube | Telescopic, stainless steel | |
| Nozzles | Crevice, upholstery and combination nozzle (1x each) | |
| Filters | Foam, pleated filter, dirt bag (1x each) | |
| Article number | 23.471.43 | |



4 006825 660067

POWER X-CHANGE
CORDLESS WET AND DRY VACUUM CLEANERS


| | TE-VC 36/30 Li S - Solo EXPERT | TE-VC 36/25 Li S - Solo EXPERT |
|---------------------------------|--|--|
| PXC battery voltage / capacity | 2x 18 V / - | 2x 18 V / - |
| Suction power | 150 mbar / 100 mbar (BOOST / ECO) | 150 mbar / 100 mbar (BOOST / ECO) |
| Tank | Stainless steel, 30 l | Stainless steel, 25 l |
| Product weight | 8.1 kg (excl. batteries) | 6.8 kg (excl. batteries) |
| Member of the PXC family | • | • |
| Automatic starting system | - | - |
| Speed settings | 2 | 2 |
| Also suitable for wet vacuuming | • | • |
| Suction hose | Plastic 250 cm, heavy-duty material | Plastic 250 cm |
| Suction tube | Telescopic, stainless steel | 2-piece, stainless steel |
| Nozzles | Crevice, upholstery and combination nozzle (1x each) | Crevice, upholstery and combination nozzle (1x each) |
| Filters | Foam, pleated filter, dirt bag (1x each) | Foam, pleated filter, dirt bag (1x each) |
| Article number | 23.471.40 | 23.471.70 |



4 006825 635874



4 006825 656527

POWER X-CHANGE
CORDLESS WET AND DRY VACUUM CLEANERS


| | TC-VC 18/20 Li S - Solo CLASSIC | TC-VC 18/15 Li - Solo CLASSIC |
|---------------------------------|--|---|
| PXC battery voltage / capacity | 18 V / - | 18 V / - |
| Suction power | 80 mbar | 80 mbar |
| Tank | Stainless steel, 20 l | Plastic, 15 l |
| Product weight | 3.6 kg (excl. battery) | 3.0 kg (excl. battery) |
| Member of the PXC family | • | • |
| Automatic starting system | - | - |
| Speed settings | 1 | 1 |
| Also suitable for wet vacuuming | • | • |
| Suction hose | Plastic 150 cm | Plastic 150 cm |
| Suction tube | 3-piece, plastic | 3-piece, plastic |
| Nozzles | Crevice, upholstery and combination nozzle (1x each) | Crevice, combination nozzle (1x each) |
| Filters | Foam, pleated filter, dirt bag (1x each) | Foam filter, filter bag, dirt bag (1x each) |
| Article number | 23.471.30 | 23.471.45 |



4 006825 625998



4 006825 652086

POWER X-CHANGE

CORDLESS WET AND DRY VACUUM CLEANERS



| | |
|---------------------------------|--|
| | TE-VC 18/10 Li - Solo EXPERT |
| PXC battery voltage / capacity | 18 V / - |
| Suction power | 90 mbar |
| Tank | Plastic, 10 l |
| Product weight | 3.1 kg (excl. battery) |
| Member of the PXC family | • |
| Automatic starting system | - |
| Speed settings | 1 |
| Also suitable for wet vacuuming | • |
| Suction hose | Plastic 200 cm |
| Suction tube | - |
| Nozzles | 2-in-1 crevice/brush nozzle and 2-in-1 upholstery/universal nozzle (1x each) |
| Filters | Foam filter, filter bag, dirt bag (1x each) |
| Article number | 23.471.60 |



4 006825 640274

POWER X-CHANGE

CORDLESS STICK VAC CLEANER



| | |
|--|---|
| | TE-SV 18 Li - Solo EXPERT |
| PXC battery voltage / capacity | 18 V / - |
| Tank volume | 0.6 l |
| Product weight | 1.1 kg (excl. battery) |
| Speed settings | 2 |
| Number of batteries / number of chargers | 0 / 0 |
| Nozzles | Motorised power brush, 2-in-1 universal nozzle, flexible crevice nozzle |
| Filters | 3-fold filter system: pre-filter, replaceable and washable pleat filter, motor filter |
| Wall bracket | • |
| Rubberised wheels | • |
| LED | • |
| Packaging | Colour box |
| Article number | 23.471.80 |



4 006825 659061

POWER XCHANGE
**CORDLESS HANDHELD
VACUUM CLEANERS**


| | TE-HV 18/06 Li - Solo EXPERT NEW | TE-VC 18 Li - Solo EXPERT |
|---------------------------------|--|---|
| PXC battery voltage / capacity | 18 V / - | 18 V / - |
| Suction power | 72 mbar / 50 mbar (BOOST / ECO) | 42 mbar |
| Tank | Plastic, 0.60 l | Plastic, 0.54 l |
| Product weight | 1.0 kg (excl. battery) | 0.9 kg (excl. battery) |
| Member of the PXC family | • | • |
| Automatic starting system | - | - |
| Speed settings | 2 | 1 |
| Also suitable for wet vacuuming | - | - |
| Suction tube | Plastic 70.0 cm | Plastic 46.5 cm |
| Nozzles | Crevice, upholstery, floor nozzle (1x each) | Crevice, upholstery, floor nozzle (1x each) |
| Filters | 1 washable synthesis filter (1x each) | 1 washable synthesis filter (1x each) |
| Wall bracket | • | • |
| Article number | 23.471.90 | 23.471.20 |



4 006825 667189



4 006825 612646

**ACCESSORIES - CORDLESS
WET AND DRY VACUUM
CLEANERS / CORDLESS
STICK VAC CLEANER**


| | Car Cleaning Set ACCESSORY | Accessories Set ACCESSORY |
|-----------------------|--|---|
| Items supplied | 7-piece set | 1 hose, 1 crevice nozzle, 1 upholstery nozzle |
| Suitable for | all Einhell Cordless Wet and Dry Vacuum Cleaners excl. TE-HV 18/06 Li and TE-VC 18 Li | TE-SV 18 Li |
| Suction hose length | 300 cm | 200 cm |
| Suction hose diameter | 36 mm | 36 mm |
| Article number | 23.512.45 | 23.512.67 |



4 006825 630121



4 006825 665017



IT'S YOUR CHOICE. WHAT DOES MULTI-AH MEAN?


Thanks to MULTI-Ah technology, switching over from a 5 Ah battery to a 8 Ah battery is really easy and can be done with just the push of a button. The 5 Ah battery has a 3x longer total service life and is suitable for lighter applications (e.g. cordless lamp or cordless screwdriver). The 8 Ah battery offers the maximum running time for more capacity-intensive applications (e.g. cordless lawn mower or cordless wet and dry vacuum cleaners)

5 Ah **300%** more service life¹⁾

8 Ah **60%** more running time²⁾

¹⁾ In comparison to every standard lithium-ion battery
²⁾ In comparison to the 5.0 Ah battery

ACCESSORIES – BATTERIES



| | 5-8 Ah Multi-Ah Power X-Change Plus Battery NEW | 4-6 Ah Multi-Ah Power X-Change Plus Battery |
|--------------------------------|--|--|
| Items supplied | 1 battery | 1 battery |
| PXC battery voltage / capacity | 18 V / 8.0 Ah or 5.0 Ah (depending on the application) | 18 V / 6.0 Ah or 4.0 Ah (depending on the application) |
| Battery power | max. 1350 W | max. 1350 W |
| Product weight | 1.04 kg | 1.02 kg |
| Article number | 45.116.00 | 45.115.02 |



4 006825 665055



4 006825 644210



ACCESSORIES – BATTERIES



| | 5.2 Ah Power X-Change Plus Battery | 4.0 Ah Power X-Change Plus Battery | 3.0 Ah Power X-Change Plus Battery |
|--------------------------------|------------------------------------|------------------------------------|------------------------------------|
| Items supplied | 1 battery | 1 battery | 1 battery |
| PXC battery voltage / capacity | 18 V / 5.2 Ah | 18 V / 4.0 Ah | 18 V / 3.0 Ah |
| Battery power | max. 1260 W | max. 900 W | max. 900 W |
| Product weight | 0.89 kg | 0.58 kg | 0.57 kg |
| Article number | 45.114.37 | 45.115.53 | 45.115.01 |



4,0 Ah BATTERY – 4,0 Ah PLUS BATTERY. WHERE'S THE DIFFERENCE?

By switching to the new "21700" cell format (21 mm diameter, 70.0 mm length) our latest Power X-Change batteries have acquired the best combination of power/running time and weight.

Why? Using this cell technology it is possible to achieve the same power and running time with five cells instead of the previous ten.

Benefits? The new batteries are 12 % lighter and 13 % more compact than their predecessors – at 100 % power and running time.

Results: Light-weight all-rounders for energy-intensive applications such as in cordless chainsaws.

4.0 Ah

4.0 Ah PLUS

- 13% more compact*
- 12% lighter*
- 100% power

* In comparison to the conventional 4.0 Ah battery

CO₂ compensated
Product
ClimatePartner.com/18088-2210-1001



Scan the barcode to receive information about the supported projects

CLIMATE PROTECTION PROJECTS AT CLIMATEPARTNER.

To compensate the CO₂ emissions of our Power X-Change batteries we are supporting climate protection projects in the areas of sustainable power generation and marine conservation. The compensation covers CO₂ emissions of the battery types 3.0 Ah Plus, 4.0 Ah Plus, 4-6 Ah Multi-Ah Plus and 5-8 Ah Multi-Ah Plus from production to sales.

The climate protection projects selected via ClimatePartner are certified in accordance with international standards such as Verified Carbon Standard (VCS) or Gold Standard (GS) and are regularly checked by independent third-parties. This assures and confirms the climate protection impact of the projects (CO₂ reduction) on a regular basis.

For detailed information use the QR code.

ACCESSORIES – BATTERIES



| | 4.0 Ah Power X-Change Battery | 2.5 Ah Power X-Change Battery | 2.0 Ah Power X-Change Battery |
|--------------------------------|-------------------------------|-------------------------------|-------------------------------|
| Items supplied | 1 battery | 1 battery | 1 battery |
| PXC battery voltage / capacity | 18 V / 4.0 Ah | 18 V / 2.5 Ah | 18 V / 2.0 Ah |
| Battery power | max. 900 W | max. 720 W | max. 450 W |
| Product weight | 0.65 kg | 0.46 kg | 0.40 kg |
| Article number | 45.113.96 | 45.115.16 | 45.113.95 |



ACCESSORIES – TWIN PACKS



| | 2x 5.2 Ah Power X-Change Twin Pack | 2x 4.0 Ah Power X-Change Twin Pack | 2x 2.5 Ah Power X-Change Twin Pack |
|--------------------------------|------------------------------------|------------------------------------|------------------------------------|
| Items supplied | 2 batteries | 2 batteries | 2 batteries |
| PXC battery voltage / capacity | 2x 18 V / 5.2 Ah | 2x 18 V / 4.0 Ah | 2x 18 V / 2.5 Ah |
| Battery power | max. 2x 1260 W | max. 2x 900 W | max. 2x 720 W |
| Product weight | 1.78 kg | 1.32 kg | 0.92 kg |
| Article number | 45.115.26 | 45.114.89 | 45.115.24 |



PXC ACCESSORIES



| | Battery Mounting Gadget | Battery Protector NEW |
|---------------------------|---|--|
| Items supplied | 2 battery mounting gadgets, 4 screws, 4 dowels | 1 battery cover |
| Suitable for (batteries) | all 18 V Power X-Change batteries | all 18 V Power X-Change batteries |
| Can be used for (devices) | - | HYPRESSO 18/24, TE-DA 18/760 Li, GE-WS 18/10 Li |
| Special feature | The batteries latch in place and are secure in every position | Protects the battery against dust and moisture |
| Article number | 45.141.55 | 41.401.51 |



ACCESSORIES – CHARGERS



| | 2x2 Power X-Quattro Charger 4 A | Power X-Twin Charger 3 A |
|-----------------------|---|---|
| Items supplied | 1 charger | 1 charger |
| Can be used for | 18 V Power X-Change batteries | 18 V Power X-Change batteries |
| Charging current | 4 A | 3 A |
| Multiple-port charger | • 4 charging slots allow 2 batteries to be charged at the same time | • 2 charging slots allow 2 batteries to be charged at the same time |
| Boost mode | - | - |
| Integrated wall mount | - | • |
| Mains voltage | 220 - 240 V ~ 50-60 Hz | 220 - 240 V ~ 50-60 Hz |
| Article number | 45.121.02 | 45.120.69 |



| | Power X-Boost Charger 8 A NEW | Power X-Boost Charger 6 A | Power X-Fastcharger 4 A |
|-----------------------|--|-------------------------------|-------------------------------|
| Items supplied | 1 charger | 1 charger | 1 charger |
| Can be used for | 18 V Power X-Change batteries | 18 V Power X-Change batteries | 18 V Power X-Change batteries |
| Charging current | 3 - 8 A | 3 - 6 A | 4 A |
| Multiple-port charger | - | - | - |
| Boost mode | • | • | - |
| Integrated wall mount | • | • | • |
| Mains voltage | 220 - 240 V ~ 50-60 Hz | 220 - 240 V ~ 50-60 Hz | 220 - 240 V ~ 50-60 Hz |
| Article number | 45.121.55 | 45.120.64 | 45.121.03 |



**OUT-AND-ABOUT AND NO POWER SOCKET AVAILABLE?
NO PROBLEM THANKS TO EINHELL!**



| | Power X-Car Charger 3 A |
|--|-------------------------------|
| Items supplied | 1 charger |
| Can be used for | 18 V Power X-Change batteries |
| Charging current | 3 A |
| Multiple-port charger | - |
| Boost mode | - |
| Protection electronics for the car battery | • |
| Integrated wall mount | • |
| Operating voltage | 12 V DC |
| Article number | 45.121.13 |



POWER X-CAR CHARGER
PROTECTION ELECTRONICS FOR THE CAR BATTERY



1. The car battery is weak:
Charging stops and both indicator lights blink in alternation – the car battery is protected from further discharge.
In this state the car can still be started.

2. The car battery is empty:
The indicator lights go out – the car battery is protected from exhaustive discharge.



ACCESSORIES – STARTER KITS



READY TO GO
IN 75 min



READY TO GO
IN 60 min

| | 2x 4.0 Ah PXC Twin Charger Starter Kit | 2x 3.0 Ah PXC Twin Charger Starter Kit |
|--------------------------------|---|---|
| Items supplied | 2 batteries + 1 Twin Charger | 2 batteries + 1 Twin Charger |
| PXC battery voltage / capacity | 2x 18 V / 2x 4.0 Ah | 2x 18 V / 2x 3.0 Ah |
| Battery power | max. 2x 900 W | max. 2x 900 W |
| Charging current | 3 A | 3 A |
| Mains voltage | 220 - 240 V ~ 50-60 Hz | 220 - 240 V ~ 50-60 Hz |
| Multiple-port charger | <ul style="list-style-type: none"> 2 charging slots allow 2 batteries to be charged at the same time | <ul style="list-style-type: none"> 2 charging slots allow 2 batteries to be charged at the same time |
| Boost mode | - | - |
| Integrated wall mount | • | • |
| Article number | 45.121.12 | 45.120.83 |



READY TO GO
IN 60 min



| | 4-6 Ah PXC Boost Charger Starter Kit NEW |
|--------------------------------|---|
| Items supplied | 1 battery + 1 Power X-Boost Charger 6 A |
| PXC battery voltage / capacity | 18 V / 6.0 Ah or 4.0 Ah (depending on the application) |
| Battery power | max. 1350 W |
| Charging current | 6 A |
| Mains voltage | 220 - 240 V ~ 50-60 Hz |
| Multiple-port charger | - |
| Boost mode | • |
| Integrated wall mount | • |
| Article number | 45.121.43 |



Ready To Go means:
The battery is ready for use. It can remain in the charger for full, low-stress charging up to 100 %.



READY TO GO
IN 80 min



READY TO GO
IN 75 min




READY TO GO
IN 50 min

| | 5.2 Ah PXC Fastcharger Starter Kit | 4.0 Ah Power X-Change Starter Kit | 2.5 Ah Power X-Change Starter Kit |
|--------------------------------|---------------------------------------|-----------------------------------|-----------------------------------|
| Items supplied | 1 battery + 1 Power X-Fastcharger 4 A | 1 battery + 1 Power X-Charger 3 A | 1 battery + 1 Power X-Charger 3 A |
| PXC battery voltage / capacity | 18 V / 5.2 Ah | 18 V / 4.0 Ah | 18 V / 2.5 Ah |
| Battery power | max. 1260 W | max. 900 W | max. 720 W |
| Charging current | 4 A | 3 A | 3 A |
| Mains voltage | 220 - 240 V ~ 50-60 Hz | 220 - 240 V ~ 50-60 Hz | 220 - 240 V ~ 50-60 Hz |
| Multiple-port charger | - | - | - |
| Boost mode | - | - | - |
| Integrated wall mount | • | • | • |
| Article number | 45.121.14 | 45.120.42 | 45.120.97 |



BATTERY RUNNING TIMES



| | | | 18 V 2.0 Ah | 18 V 2.5 Ah | 18 V 3.0 Ah | 18 V 4.0 Ah | 18 V 5.2 Ah | 18 V 6.0 Ah | 18 V 8.0 Ah |
|--------------------------------------|-----------------------|--------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| Cordless Impact Wrenches | IMPAXXO 18/400 | | 55 pcs | 68 pcs | 80 pcs | 110 pcs | 140 pcs | 160 pcs | 220 pcs |
| | IMPAXXO 18/230 | | 100 pcs | 125 pcs | 150 pcs | 200 pcs | 260 pcs | 300 pcs | 400 pcs |
| Cordless Car Polishing Machine | CE-CB 18/254 Li | | 81 min | 93 min | 112 min | 127 min | 200 min | 222 min | 254 min |
| Cordless Polishing/Sanding Machine | CE-CP 18/180 Li E | | 20 min | 25 min | 35 min | 43 min | 54 min | 65 min | 86 min |
| Cordless Air Pump | CE-AP 18 Li | | 65 min | 81 min | 98 min | 130 min | 169 min | 195 min | 260 min |
| Cordless Car Compressor | CE-CC 18 Li | | 42 min | 53 min | 63 min | 84 min | 109 min | 126 min | 168 min |
| Cordless Compressors | TE-AC 36/150 Li OF | | - | 26 | 36 | 45 | 54 | 72 | 90 |
| | | | - | 410 pcs | 600 pcs | 720 pcs | 850 pcs | 1200 pcs | 1440 pcs |
| | TE-AC 36/8 Li OF | | 8 min | 10 min | 12 min | 16 min | 21 min | 24 min | 32 min |
| | | | 6 min | 7.5 min | 9 min | 12 min | 15 min | 18 min | 24 min |
| 6-in-1 Cordless Hybrid Compressors | PRESSITO 18/25 Hybrid | | 22 min | 28 min | 34 min | 44 min | 58 min | 68 min | 88 min |
| | PRESSITO | | 30 min | 37 min | 45 min | 60 min | 85 min | 90 min | 120 min |
| 3-in-1 Cordless Compressors | PRESSITO 18/25 | | 22 min | 28 min | 34 min | 44 min | 58 min | 68 min | 88 min |
| | PRESSITO 18/21 | | 30 min | 37 min | 45 min | 60 min | 85 min | 90 min | 120 min |
| Cordless Wet and Dry Vacuum Cleaners | TP-VC 36/30 S Auto | | 8 min | 10 min | 12 min | 16 min | 21 min | 24 min | 32 min |
| | | | 11 min | 13 min | 16 min | 22 min | 28 min | 33 min | 44 min |
| | TE-VC 36/30 Li S | | 8 min | 10 min | 12 min | 16 min | 21 min | 24 min | 32 min |
| | | | 11 min | 13 min | 16 min | 22 min | 28 min | 33 min | 44 min |
| | TE-VC 36/25 Li S | | 8 min | 10 min | 12 min | 16 min | 21 min | 24 min | 32 min |
| | | | 11 min | 13 min | 16 min | 22 min | 28 min | 33 min | 44 min |
| TC-VC 18/20 Li S | | 10 min | 11 min | 16 min | 20 min | 25 min | 32 min | 40 min | |
| TC-VC 18/15 Li | | 10 min | 11 min | 16 min | 20 min | 25 min | 32 min | 40 min | |
| TE-VC 18/10 Li | | 10 min | 12 min | 17 min | 21 min | 26 min | 30 min | 42 min | |
| Cordless Stick Vac Cleaner | TE-SV 18 Li | | 11 min | 13 min | 18 min | 22 min | 28 min | 35 min | 44 min |
| | | | 25 min | 31 min | 38 min | 50 min | 65 min | 80 min | 100 min |
| Cordless Handheld Vacuum Cleaners | TE-HV 18/06 Li | | 12 min | 15 min | 19 min | 25 min | 32 min | 39 min | 50 min |
| | | | 22 min | 26 min | 33 min | 44 min | 54 min | 65 min | 88 min |
| TE-VC 18 Li | | 16 min | 18 min | 23 min | 31 min | 40 min | 46 min | 62 min | |

81 min

BASIC PERFORMANCE – Upgrade recommended

Figures shown in lighter fields (for example see above) indicate that we recommend using a battery with greater power/capacity for full power and the appropriate operating time of the machine.

All stated values are maximum values. They were determined under standardised test conditions and may differ from the values achievable in everyday operation.

Key to Symbol:

- Tightening/loosening wheel bolts (hexagon head, size 22 mm) – max. quantity per battery charge
- Max. operating time per battery charge in idle mode
- Max. idling time per battery charge in BOOST / ECO mode
- Max. number of inflation cycles by the compressor per battery charge
- 13 mm staples in softwood at maximum depth setting – max. number per battery charge
- Max. running time when using a blow-out pistol
- Max. running time when inflating a car tyre to 2.5 bar

BATTERY CHARGING TIMES



| | 1.5 Ah | 2.0 Ah | 2.5 Ah | 3.0 Ah | 4.0 Ah | 5.2 Ah | 6.0 Ah | 8.0 Ah | |
|--|--------|--------|--------|--------|--------|---------|---------|---------|------------------------------|
| Power X-Charger 3 A | | | | | | | | | Shorter charging time |
| Power X-Twincharger 3 A (Charging 2 batteries simultaneously) | 30 min | 40 min | 50 min | 60 min | 75 min | 100 min | 120 min | 160 min | |
| Power X-Car Charger 3 A | | | | | | | | | -25% |
| Power X-Fastcharger 4 A | 24 min | 30 min | 37 min | 45 min | 60 min | 80 min | 90 min | 120 min | |
| 2x2 Power X-Quattrocharger 4 A (Charging 2 batteries simultaneously) | | | | | | | | | -50% |
| Power X-Boostcharger 6 A * | 24 min | 30 min | 27 min | 32 min | 40 min | 50 min | 60 min | 80 min | |
| Power X-Boostcharger 8 A ** | 24 min | 30 min | 27 min | 32 min | 40 min | 40 min | 45 min | 60 min | -60% |

* Only 2.5 Ah - 8.0 Ah batteries can be charged with 6 A. Batteries of lower capacity are charged with a lower current.

** Only 5.2 Ah - 8.0 Ah batteries can be charged with 8 A. Batteries of lower capacity are charged with a lower current.





Einhell

CORDLESS EXCELLENCE.

POWER X-CHANGE

TWO PARTNERS. ONE MISSION.
MAXIMUM PERFORMANCE.



EINHELL IS A PROUD PARTNER OF
MERCEDES-AMG PETRONAS F1 TEAM.

Official Tool Expert



AMG
PETRONAS
FORMULA ONE TEAM

CHARGING SYSTEMS AND CAR ACCESSORIES 2023/2024

Is there anything you´d like to ask us about our products?
Would you like to order a part?
Your product isn´t working as it should?

We´re at your service!
We´ll get you some help – fast and without any fuss.



Einhell-Service
Eschenstr. 6
94405 Landau/Isar
Germany



+ 49 (0) 9951 959 2000



+ 49 (0) 9951 959 1700



www.einhell-service.de



Service-DE@einhell.com

Einhell Germany AG
Wiesenweg 22
94405 Landau / Isar
Germany
info@einhell.de – www.einhell.de